

Flexxomat TT/TT-C

Function: Semi- and fully automatic fillable disinfection mat for internal transport traffic.

The Flexxomat T disinfection mat is the preventive hygiene solution for passenger and transport traffic in the food industry, greenhouse horticulture, agriculture and laboratories. In addition, it is also very suitable in places where many people come together, such as large events, trade fairs and airports. In the context of quality management systems such as HACCP, BRC, IFS, GSP and ISO 22000, risk and high care zones of production companies can be better protected against the introduction of micro-organisms and their possible consequences.



The Flexxomat T is unique and can be used for various types of (internal) transport, where the mat, due to its innovative design and reinforcements (patented), does not need to be secured to the surface. For an effective and disinfectant-efficient use, but also for a good cleaning, the Flexxomat T can be equipped with an internal fluid distribution tunnel. The mat can then be connected to a dosing pump via an external hose connector (for disinfection supply or for cleaning by flushing with water).

The Flexxomat TT is filled semi-automatically (by a timer-controlled pump).

The Flexxomat TT-C is filled fully automatically (by a sensor-controlled pump). Keeping the disinfection liquid in the mat up to the required level is thus ensured at all times.

Flexxolutions has more than 15 years of experience in the development and production of disinfection mats and, in addition to standard sizes, also offers customer-specific custom solutions.

Technical specifications Flexxomat TT/TT-C

Version/data	L221*B100	L221*B200	L221*B300	L221*B400	L221*B500	L221*B600
Liquid tunnel	TT/TT-C	TT/TT-C	TT/TT-C	TT/TT-C	TT/TT-C	TT/TT-C
Filling sensors	TT-C only	TT-C only	TT-C only	TT-C only	TT-C only	TT-C only
Thickness	±1 cm	±1 cm	±1 cm	±1 cm	±1 cm	±1 cm
Length	221 cm	221 cm	221 cm	221 cm	221 cm	221 cm
Width	100 cm	200 cm	300 cm	400 cm	500 cm	600 cm
Weight	±15 kg	±25 kg	±35 kg	±45 kg	±55 kg	±65 kg
Fluid supply	Up to 5 l/m ²	Up to 5 l/m ²	Up to 5 l/m ²	Up to 5 l/m ²	Up to 5 l/m ²	Up to 5 l/m ²
Pack (l*w*h, cm)	±230*27*15	±230*27*15	±305*27*15	±405*27*15	±505*27*15	±605*27*15
Bottom/sides	Liquid-tight and anti-slip					
Top side	Permeable, wear-resistant, UV-resistant and evaporation inhibiting					
Mat core	Liquid absorbing stable core material					

Customized dimensions available on request.